



# Snetor



## HUZUR

www.huzurplastik.com

info@huzurplastik.com

+90 212 444 14 97

# LLDPE

## LLD-0219AB

### Technical Data Sheet

Snetor LLD-0219AB is a butene LLDPE resin with excellent mechanical and sealing properties. This material contains 1000 ppm slip and 5500 ppm anti-block. It can be used in can liner applications, and is suitable for blending with LDPE in packaging applications.

**Application Uses:** Blend stock and Food packaging.

FDA Compliant

Kosher Compliant

NOMINAL RESIN PROPERTIES	NOMINAL VALUE (SI)	METHOD (ASTM)
Density	919 kg/m <sup>3</sup> (0.919 g/cm <sup>3</sup> )	D1505
Melt Index	2.0 g/10min	D1238
Haze	20.0%	D1003
Dart Impact	110 g/mil	D1709
Tensile Break		
MD	4,000 psi	D882
TD	3,100 psi	D882
Ultimate Elongation		
MD	700%	D 882
TD	900%	D 882
1% Secant Modulus		
MD	28,000 psi	D882
TD	31,000 psi	D882



**Snetor**  
USA

One River Way, Ste 1125 -  
Houston, TX, 77056 - USA  
Email: [plastics@snetor.fr](mailto:plastics@snetor.fr)



**Snetor**  
chimie

Tel : +33 1 49 04 88 88  
Email: [plastics@snetor.fr](mailto:plastics@snetor.fr)

#### Disclaimer :

The information on this document is, to our knowledge, true and accurate. Due to operating conditions and intended uses beyond our control, it is the customer's responsibility to establish satisfactory performance of this product for the intended application. By providing the information contained herein, SNETOR, makes no guaranty or warranty, and does not assume any liability with respect to the completeness of such information.