

LLD-2420N

LinearLow Density Polyethylene (LLDPE)

Technical Data Sheet

The Snetor LLD-2420N is a butene LLDPE with excellent mechanical and sealing properties.

Main uses:

- Blend stock
- Food packaging
- Stretch wrap

FDA Accepted.

NOMINAL RESIN PROPERTIES	NOMINAL VALUE (SI)	METHOD
Density	0.919 g/cm ³	ASTM D1505
Melt Index	2.0 g / 10 min	ASTM D1238
Haze	13%	ASTM D1003
Dart impact	110g/mil	ASTM D1709
Tensile Break MD	4,000 psi	ASTM D882
Tensile Break TD	3,100 psi	ASTM D882
Ultimate Elongation MD	700%	ASTM D882
Ultimate Elongation TD	900%	ASTM D882
1% Secant Modulus MD	28,000	ASTM D882



Snetor
USA

One River Way, Ste 1125 -
Houston, TX, 77056 - USA
Email: plastics@snetor.fr



Snetor
chimie

Tel : +33 1 49 04 88 88
Email: plastics@snetor.fr

Disclaimer :

The information on this document is, to our knowledge, true and accurate. Due to operating conditions and intended uses beyond our control, it is the customer's responsibility to establish satisfactory performance of this product for the intended application. By providing the information contained herein, SNETOR, makes no guaranty or warranty, and does not assume any liability with respect to the completeness of such information.