



engro polymer & chemicals

SABZ PVC AU-67R

AU-67R is a medium molecular weight suspension resin. It has a narrow range of particle size distribution, high bulk density, and excellent dry-flow properties. This results into a high and uniform production rate in the extrusion process. This grade has been specially designed, and is recommended for, rigid PVC applications.

TYPICAL PROPERTIES

Property	Value	Test Method*
K-Value	66 \pm 1	DIN 53726
Appearance	White	-----
Bulk Density g/cc	0.54 - 0.58	JIS K6721
Volatile Matter	Max. 0.4%	JIS K6721
Particle Size		
Passes 40 mesh	100%	EAPCL Method
Passes 270 mesh max.	3%	

* DIN :German Standards

JIS: Japanese Industrial Standards

APPLICATIONS

Rigid PVC pipes, conduits and ducting, PVC profiles such as doors, windows and other sections, PVC corrugated pipes, PVC shrinkable film and also twist wrap candy film, rigid PVC compounds for extrusion.

The technical data mentioned above is the result of tests conducted in accordance with the standard testing procedures, and has been provided to enable customers to make the best use of this data. The Company does not guarantee, or assume any responsibility for, the end results.

Tel: 111-411-411 / 5610743, 5610610
Fax: 5611600